SUBJECT: **INSTITUTIONAL STANDARD ON WATER-SAVING TOILET FIXTURES**			
DOCUMENT TYPE: **REPORT**	DATE OF REPORT: **AUGUST 7, 2024**	SUPERSEDES: N/A	CC: **OSP, OEVP, OAA, CIPQ**

1. OBJECTIVE

To minimize water use in HCCCI campus restrooms through the provision of dual-flush toilet fixtures that offer a reduced-flush option and a full-flush option.

2. SCOPE

The fixture requirement covers all restrooms in HCCCI's three-storey campus building. The institution has confirmed that dual-flush toilets are installed in all campus restrooms.

3. INSTITUTIONAL FIXTURE STANDARD

All campus restrooms shall be provided with dual-flush toilets. Each toilet shall offer a 3-litre reduced flush for liquid waste and a 6-litre full flush for solid waste, allowing users to select the appropriate flush according to need. The LA FONZA toilet is the documented example of an installed unit.

4. DOCUMENTED APPLICATION

The supplied photographs show a LA FONZA toilet with a two-button flush control and a representative campus toilet cubicle. HCCCI reports flush volumes of 3 L reduced / 6 L full. A handheld bidet and a manual wall-mounted faucet are also visible; no flow-rate classification is assigned to these accompanying fixtures.

PREPARED BY:	NOTED BY:	APPROVED BY:
ENGR. KIRBY CLEM L. BARRIGA *Safety Officer* Date: 08-07-2024	**VANESSA MARIE L. ANTIQUIN, MMEM** *Executive Vice President* Date: 08-07-2024	**MARIVET S. CABALLERO** *School President* Date: 08-09-2024



Figure 1. Toilet Facility with Water-Efficient Plumbing Fixtures.
The restroom facility of Holy Child Central Colleges, Inc. (HCCCI) features a toilet equipped with a dual-flush mechanism, a handheld bidet sprayer, and functional plumbing fixtures. These installations support the institution's efforts to promote responsible water consumption and minimize unnecessary water use within campus facilities.



Figure 2. Dual-Flush Water Conservation Mechanism.
A close-up view of the LA FONZA toilet's dual-flush system, featuring two flushing options designed to regulate the volume of water released according to usage requirements. This mechanism demonstrates the integration of water-saving features into the institution's sanitation facilities, supporting efficient water management and sustainable building practices.